

8U 50/74 Bay

NSR 850/874

SUPPORTS SATA/SAS 12Gb/s

technical specifications



Maximizing Possibilities with Ci Design's Storage Chassis

Introducing the all new Ci Design NSR 850/874 high performance, high capacity storage server system that supports **up to 74 hot-swappable hard disk trays**, and accomodates a wide range of server boards.

Features

Ela & SSI compliant 8U Form Factor

Standard M/B Support: Up to 13" x 13.68"
Optional M/B Support: Extended aTX 13" x 16"

Supports up to 74 hot-swappable
3.5" HDD trays (48 front, 24x3.5"+2x2.5" rear)

Integrated backplane design which
supports SaTa 3Gb/s or SaTa/SaS 6Gb/s, SAS 12Gb/s

Redundant 1780W - Standard*

advanced thermal design with hot-swappable fans

Shock and vibration-resistant design

Specifications

Hard Drive Trays

50 Hot-Swappable HDD Trays
(48 front, 2X2.5" rear)

or

74 Hot-Swappable HDD Trays
(48 front, 24x3.5"+2x2.5")

Backplane Interface Options

SATA / SAS 6Gb/s /SAS 12Gb

Dimensions

8U Form Factor - 29" (L) x 17" (W) x 14" (H)

Ventilation

6 x Fans (92mm x 92mm x 38mm)

* Certain configurations may require more power.



Copyright © 2010 Ci Design. Ci Design is a registered trademark of Commercial and Industrial Design Co., Inc. All rights reserved. All other trademarks, trade names or company names referenced herein are used for identification purposes only and are the property of their respective owners. All products, dates, specifications, features, and figures specified are based on ideal conditions and are subject to change without notice.

US Headquarters
20 Odyssey, Irvine, CA 92618, USA
TEL 949.872.2555
FAX 949.679.1572
TOLL Free 1.800.576.5487
info@cidesign.com

Europe Headquarters
Polychemstraat 4,
6191 NL Beek (LB), The Netherlands
TEL 31.46.477. 0640
FAX 31.46.477.0649
info@ci-designeurope.nl

Asia Headquarters
27, 10th FL, Lane 61, Kung Fu Rd,
Sec 1, Sanchung City, Taipei, Taiwan
TEL 886.2.2999.2152
FAX 886.2.2999.2465
mtcsales@majestic.com.tw

Visit us on the web at
www.CiDesign.com

2 HDD Trays
(NSR 850)



24 HDD Trays
(NSR 874)

